

## A

absorptance  
  definition, 78  
  determinants of, 78–79  
  energy performance and, 78  
  optical properties database, 76  
  tinted glass, 84

acoustical properties of windows, 60–61

acrylic glazing material, 81

aerogel windows, 110–11

Air Conditioning Contractors of America, 224

air infiltration  
  condensation and, 62  
  definition, 36, 46  
  determinants, 36, 125  
  energy effects, 46–48  
  IECC 2006 requirements, 25  
  measurement, 47, 48  
  sound control and, 60  
  sources of discomfort, 53  
  window type characteristics, 123–24

Alliance to Save Energy, 222

aluminum window frames, 126, 128–30, 136–38

American Architectural Manufacturers Association,  
  65, 220  
  standards, 224

American Institute of Architects, 19, 220

American National Standards Institute, 220

American Society for Testing and Materials, 70, 220,  
  224–25  
  sound transmission standards, 60–61  
  window installation standards, 138

American Society of Heating, Refrigerating and Air  
  Conditioning, Inc. (ASHRAE), 220  
  standards, 55, 217, 224

American Solar Energy Society, 220

angle of window surface  
  heat transfer and, 38  
  reflectance and, 76

appearance, 33  
  elements of, 34–35  
  house design, 148  
  views through windows, 149–51

argon gas, 97

awning windows, 120, 123, 154, 162

## B

building codes, 71

Building Codes Assistance Project, 24

building energy codes, 22–24  
  IECC 2006 codes, 25–27

## C

Canadian professional organizations, 221, 225

casement windows, 120, 123

Center for Sustainable Building Research, 222

Center for the Built Environment, 56–57

clarity of glazing, 35

clerestory window, 152

climate zones and conditions, 174  
  ENERGY STAR program, 30  
  high altitude window installation, 145–46  
  in 2006 IECC, 25  
  north/central zone, 184–91  
  northern zone, 176–83  
  south/central zone, 192–99  
  southern zone, 200–207  
  summer heat gain controls, 159–66  
  sunlight patterns, 152–53  
  typical house energy performance, 31  
  ventilation considerations, 157–59  
  winter heat gain strategies, 169–73  
  *see also* wind conditions

coatings and glazings  
  absorptance, 78–79  
  condensation risk, 62–63  
  fading effects, 68  
  glass surface temperature, 54  
  performance comparison of glazing types, 106–8  
  reflective, 86–87  
  reflectivity, 77–78  
  smart windows, 16  
  solar control, 15  
  transmittance and, 49, 51, 74–75  
  *see also* low-E coatings

color, glass, 35, 80

computer simulations, 65, 219–20

condensation  
  air infiltration and, 62  
  causes, 61  
  between glazings, 66–67  
  glazing type and, 62–65  
  on interior frames, 62  
  interior humidity and, 61  
  outdoor, 66  
  problems caused by, 61, 62  
  resistance rating, 65  
  in skylights and roof windows, 62

conduction  
  definition, 35  
  measurement, 36

convection  
  definition, 35  
  in heat transfer, 37  
  measurement, 36

cost-savings calculations  
  air leakage effects, 47  
  frame materials, 136–38  
  glazing area, 17–18, 161–62, 166  
  life-cycle analysis, 208–10  
  national energy use, 19–21

- north/central climate zone energy performance, 184–91
  - northern climate zone energy performance, 176–83
  - performance comparison of glazing types, 106–8
  - shading conditions, 172–73
  - smart windows, 115–16
  - solar heat gain coefficient, 46*f*
  - south/central climate zone energy performance, 192–99
  - southern climate zone energy performance, 200–207
  - summer heat gain control strategies, 165–66
  - window orientation, 159, 170–72
  - for window selection, 8, 174, 175
  - winter solar gain strategies, 170–73
- D
- daylight, 151–56
  - Department of Energy, U.S., 7, 17, 24, 217, 222
  - Department of Housing and Urban Development, U.S., 226
  - diffusion of direct sunlight, 154–55
  - distortion, optical, 35
  - DOE-2.1E, 220
  - double-glazed windows
    - blinds in, 163–64
    - condensation risk, 62–63, 66–67
    - fading effects, 68*f*
    - heat transfer effects, 37
    - performance comparison of glazing types, 106–8
    - properties, 87–88
    - solar heat gain coefficient, 45*f*
    - technical evolution, 14, 88
    - thermal comfort index, 57
    - tinted glazing in, 89–90
    - transmittance, 50*f*
    - U-factors, 38–39
  - double-hung windows, 120, 124
  - drafts, 37, 52*f*, 53, 167
  - drapes, 154, 162–63, 167
  - durability of windows, 69–70, 98, 223
- E
- edge effects, 40, 103
  - Efficient Windows Collaborative, 7, 28, 29, 31, 175
  - electrochromic glazing, 16–17, 114–17
  - electromagnetic spectrum, 73
  - emergency exits, 126
  - emittance
    - definition, 79
    - energy performance and, 72, 79
    - optical properties database, 76
    - see also* low-E coatings
  - Energy & Environmental Building Association, 138
  - energy performance
    - building energy codes, 22–27
    - current state, 9
    - determinants, 33, 35–36, 72–73. *see also specific factor*
    - durability of windows and, 69–70
    - evolution of house design, 10–11
    - frame materials and, 136–38
    - future prospects, 16–17
    - glazing area and, 17–18, 161–62, 166
    - glazing technology to improve, 82
    - life-cycle cost calculations, 209–10
    - modeling software, 219–20
    - in north/central climate zone, 184–91
    - in northern climate zone, 176–83
    - rating systems, 7, 27
    - recent technical improvements, 15–16
    - in south/central climate zone, 192–99
    - in southern climate zone, 200–207
    - summer heat gain control, house design for, 159–66
    - sustainable building movement, 21–22
    - technical evolution, 14–15
    - voluntary building energy-efficiency programs, 27–28
    - window installation as factor in, 138
    - as window selection criterion, 174, 175
    - window types, 123–24
    - winter heat gain strategies, 169–73
    - winter heat loss control strategies, 166–69
    - see also* heat transfer; high-performance windows
  - ENERGY STAR Windows, 7, 28, 175, 222
    - essential elements, 30
    - north/central climate zone requirements, 184
    - northern climate zone requirements, 176
    - south/central climate zone requirements, 192
    - southern climate zone requirements, 200
  - Environmental Protection Agency, 30
  - evacuated windows, 108–10
- F
- fiberglass window frames, 135
  - flashing, 140–42
  - float glass, 14, 80
  - Florida Solar Energy Center, 222
  - fossil fuel use, 20
  - frames. *see* sash and frame design
  - French door, 13, 120, 124
  - future of window technology, 16–17
    - glazing materials and treatments, 108–17
    - Lawrence Berkeley National Laboratories website, 108
    - self-cleaning glass, 117
- G
- garden windows, 121
  - gas-filled windows

- evacuated windows, 108–10
- gas characteristics, 97–98
- long-term performance, 98
- performance comparison, 98–100
- purpose, 15, 96–97
- glare, 52, 153–54
- Glass Association of North America, 220
- glassmaking
  - historical and technical evolution, 12–13, 79–80
  - tinted glass, 83
- glass properties
  - absorptance, 78–79
  - aesthetic considerations, 35
  - clear single glazing, 83
  - color, 35, 80
  - condensation risk, 62–65
  - emittance, 79
  - energy performance determinants, 72, 73–74
  - fading effects, 67–69, 75
  - future prospects, 108–17
  - heat strengthening, 80
  - iron content, 80
  - optical properties database, 76
  - performance comparison, 106–8
  - plastic properties vs., 81
  - reflectance, 76–78
  - solar heat gain coefficient, 45<sup>f</sup>
  - tempering, 80
  - thermal comfort index, 57
  - tinted glass, 83–86
  - translucent materials, 155
  - transmittance, 49–51, 50<sup>f</sup>, 73, 74–76
  - U-factors, 38–39
- Green Building Initiative, 22
- greenhouse windows, 121
- H
- haze, 35
- heat-strengthened glass, 80
- heat transfer
  - in aluminum window frames, 128–29
  - emissivity of glass, 79
  - glazing material properties and, 73–74
  - low-E coatings, 15
  - measurement of insulating value, 38–40
  - mechanisms, 35–38. *see also specific mechanism*
  - tinted glass, 84
- high-performance windows
  - benefits, 8, 16, 17–18
  - current utilization, 7
  - glass surface temperature, 55
  - house design considerations, 11, 147–48
  - net zero energy window, 17
  - rationale, 19–21
  - technologies, 15–16
  - tinting, 85–86
  - see also* spectrally selective glass
- hinged windows, 120, 123
- hopper windows, 120, 123
- house design
  - air leakage risk, 47–48
  - building energy codes, 22–27
  - environmental considerations, 10–11
  - glazing area, 161–62, 166
  - heat loss control strategies, 166–69
  - with high-performance windows, 147–48
  - historical and conceptual evolution, 10–11, 14
  - lighting considerations, 151–56
  - north/central climate zone energy performance comparison, 187–90
  - northern climate zone energy performance comparison, 180–82
  - privacy considerations, 150–51
  - RESFEN modeling assumptions, 211–13
  - security considerations, 150
  - south/central climate zone energy performance comparison, 195–98
  - southern climate zone energy performance comparison, 203–6
  - summer heat gain controls, 159–66
  - sustainable building movement, 21–22
  - ventilation considerations, 156–59
  - view from windows, 149–51
  - voluntary building energy-efficiency programs, 27–28
  - window selection criteria, 148–49
  - winter heat gain strategies, 169–73
- human factors
  - acoustical properties of windows, 60–61
  - transmittance, 49–51
  - ventilation function of windows, 59
  - in window selection, 33
  - see also* thermal comfort
- I
- IECC. *see* International Energy Conservation Code
- IGMA certification, 70
- IGU certification, 70
- installation of windows
  - air barrier and water vapor retarders, 142–43
  - energy performance and, 138
  - general guidelines, 140
  - goals, 138
  - at higher altitudes, 145–46
  - information resources, 138
  - insulation, 142
  - replacement windows and sashes, 143–44
  - resources, 223
  - skylights, 144–45
  - water control in, 138–42
- insulated glazing, 14, 70
- Insulating Glass Manufacturers Alliance, 221

- insulating value
  - definition, 36
  - determinants, 36–39
  - measurement. *see* U-factor
  - vinyl window frames, 133
- insulation around windows, 142
- insulation panels, 168
- International Code Council, 23, 220, 225
- International Energy Conservation Code (IECC), 23, 24, 217
  - 2006 standards, 25–27
- International Standards Organization, 221, 225
- K**
- krypton gas, 17, 97
- L**
- laminated glass, 71, 80, 105–6
- landscaping, 153, 164, 172
- Lawrence Berkeley National Laboratories, 17, 108, 222
- leakage. *see* air infiltration; water resistance
- LEED for Homes™, 22
- life-cycle cost analysis, 208–10
- lighting design, 151–56
- light-to-solar-gain ratio, 51
- light tubes, 121, 155
- liquid crystal glazing, 113
- long-term performance, 33
  - gas-filled windows, 98
  - life-cycle cost analysis, 208–10
- low-E coatings
  - coating placement, 93–94
  - coating types, 92–93
  - condensation risk, 62–63
  - definition and function, 15
  - emittance, 79
  - energy performance effects, 90–91, 96, 100
  - fading effects, 69
  - glass color, 35
  - glass surface temperature, 55
  - laminated glazing, 105–6
  - origins and development, 14
  - performance comparison of glazing types, 106–8
  - reflectance, 76–77
  - solar gain properties, 94–96
  - thermal comfort index, 57–59
  - transmittance, 51
  - triple-glazed windows, 104–5
- M**
- maintenance requirements, 70–71
  - cost calculations, 209
  - future of window technology, 117
- market transformation programs, 28
- materials of manufacture
  - aesthetic considerations, 34–35
  - aluminum, 128–30
  - composite and hybrid designs, 133–35
  - energy performance, 127, 136–38
  - evolution, 126–27
  - spacers, 101–2
  - types of frame materials, 118*f*
  - vinyl, 131–33
  - wood, 130–31
- Model Energy Code, 23
- mortgage rates, 24
- museum light, 69
- N**
- NAHB Green Building Guidelines, 22
- National Association of Home Builders, 220
- National Energy Policy Act, 217
- National Fenestration Rating Council, 7, 28, 214, 221
  - condensation resistance rating, 65
  - label, 31, 175
  - standards, 225–26
  - testing and certification, 214–15, 217, 218
  - transmittance ratings, 50
- National Renewable Energy Laboratory, 222
- National Technical Information Service, 222
- net zero energy window, 17
- north/central climate zone, 184–91
- northern climate zone, 176–83
- O**
- Oak Ridge National Laboratory, 222
- optical properties database, 76
- overhangs, 162
- P**
- particle dispersed glazing, 113
- patio doors, 120
- photochromic materials, 112
- photopic sensitivity, 75
- placement, windows
  - evolution of house design, 10–11
  - lighting considerations, 151–56
  - for summer heat gain control, 159–66
  - ventilation considerations, 156–59
  - for winter heat gain, 169–72
- plastic glazing materials, 81–82
  - laminated glazing, 103–4, 105–6
  - low-E coatings, 93
- plastic window frames. *see* thermoplastic frames; vinyl frames
- polycarbonate glazing material, 81
- polyester glazing material, 82
- polyvinyl chloride. *see* vinyl frames
- privacy considerations, 150–51
- projected windows, 120
- pyrolytic coatings, 92–93, 94–95

## Q

quadruple-glazed windows, 100, 103

## R

radiant asymmetry, 53

radiation

definition, 35

fading effects, 67–69, 75

heat transfer, 37–38

measurement, 36

in solar heat gain, 43

ratings

condensation resistance, 65

durability standards, 70

energy performance, 7, 27

quantifying thermal comfort, 54–56

sound transmission, 60–61

*see also* National Fenestration Rating Council

reflectance

glazing properties and, 76–78

low-E coatings, 15

optical properties database, 76

reflective glazing, 86–87

regulations

building energy codes, 22–24

codes and standards, 224–26

ventilation requirements, 156

replacement windows and sashes, 143–44

RESCheck, 25

RESFEN, 8, 32, 175, 219

modeling assumptions, 211–13

north/central climate zone energy performance  
comparison, 184–91

northern climate zone energy performance  
comparison, 176–83

south/central climate zone energy performance  
comparison, 192–99

southern climate zone energy performance  
comparison, 200–207

Responsible Energy Codes Alliance, 24, 221

R-value, 38

## S

sash and frame design

air leakage, 48

condensation problems, 62, 65

heat transfer mechanism, 40

high-performance design, 16

maintenance requirements, 70–71

skylights and roof windows, 121

types of materials, 118*f*

types of windows, 119–24

water resistance, 71

weatherstripping, 124–25

*see also* installation of windows

seal technology

double-seal systems, 101

single-seal systems, 101

technical evolution, 14, 88

*see also* spacers

security considerations, 126, 150

selection, window

building energy codes and, 22

cost considerations, 174, 175

determinants, 8, 29, 33, 174

durability considerations, 69–70

energy performance considerations, 174, 175

gas-filled windows, 98–100

house design considerations, 148–49

maintenance considerations, 70–71

for north/central climate zone, 184–91

for northern climate zone, 176–83

performance comparison of glazing types, 106–8

for south/central climate zone, 192–99

for southern climate zone, 200–207

step-by-step guide, 29–32

thermal comfort comparisons, 56–59

tools, 8

self-cleaning glass, 117

shades and blinds, 154, 162–64

heat loss control, 167–68

shading

to increase solar gain, 172–73

to reduce heat gain, 162–66

shading coefficient, 36, 43, 44

single-hung windows, 120, 124

skylights and roof windows

angle, 38

condensation problems, 62

design characteristics, 121

installation, 144–45

light diffusion, 155

light tubes, 121

north/central climate zone energy performance  
comparison, 191

northern climate zone energy performance  
comparison, 183

performance comparison, 108

south/central climate zone energy performance  
comparison, 199

southern climate zone energy performance  
comparison, 207

sliding glass doors, 120, 124

sliding windows, 120, 124

smart windows, 16–17, 111–17

solar heat gain coefficient

clear single glazing, 83*f*

definition, 36

determinants, 43, 44

double-glazed windows, 87*f*, 89–90

energy effects, 45–46

- house design for summer heat gain control, 159–66
  - IECC 2006 requirements, 25, 27
  - light-to-solar-gain ratio, 51
  - low-E coatings, 94–96
  - measurement, 43, 44–45
  - reflective coatings, 86–87
  - significance, 43
  - tinted glass, 84*f*, 89–90
  - solariums, 122
  - sound control, 60–61
  - south/central climate zone, 192–99
  - southern climate zone, 200–207
  - spacers
    - condensation risk, 63
    - functions, 100
    - heat transfer, 40, 98–100, 101, 103
    - single-seal system, 101
    - technical evolution, 88, 100–102
    - warm edge, 16, 98, 102–3
  - spectrally selective glass, 85, 89–90. *see also* low-E coatings
  - sputtered coatings, 92
  - sun rooms, 122
  - surface temperature of glass, 54, 55
  - sustainable building movement, 21–22
  - Sustainable Buildings Industry Council, 221
- T
- tax credits, 28
  - Tax Incentives Assistance Project, 28
  - tempered glass, 80
  - thermal breaks, 129
  - thermal comfort
    - determinants, 52
    - measurement, 54–56
    - product comparison, 56–59
    - significance of, 52
    - sources of discomfort, 53–54
  - thermal radiation. *see* radiation
  - thermochromic materials, 112–13
  - thermography, 98–100
  - thermoplastic frames, 135
  - THERM 5 software, 65, 219–20
  - tinted glass, 35, 83–86
    - with double-glazing, 89–90
  - translucent glazing, 155
  - transmittance, 49–51
    - clear single glazing, 83*f*
    - definition, 49, 74
    - determinants, 49
    - double-glazed windows, 87*f*, 89–90
    - electrochromic glazing, 114, 116
    - energy performance effects, 73
    - glazing properties and, 76
    - goals, 49–50
    - light-to-solar-gain ratio, 51
    - low-E coatings, 90–91, 96
    - measurement, 50
    - optical properties database, 76
    - reflective coatings, 87
    - tinted glass, 84, 85–86, 89–90
    - ultraviolet, 75
    - visible light, 73, 74–75
  - transportation of manufactured windows, 145
  - trickle ventilators, 157
  - triple-glazed windows, 14
    - condensation risk, 62–63
    - effectiveness, 103
    - fading effects, 68*f*
    - with low-E coatings, 104–5
    - solar heat gain coefficient, 45*f*
    - thermal comfort index, 57
    - transmittance, 50*f*
    - U-factors, 38–39
- U
- U-factor
- aluminum window frames, 129
  - center-of-glass, 39–40
  - clear single glazing, 83*f*
  - computer simulations, 65
  - definition, 38
  - determinants, 38–40
  - double-glazed windows, 87*f*, 89–90
  - energy effects, 42–43
  - frame materials and, 127
  - IECC 2006 requirements, 25, 27
  - low-E coatings, 96
  - overall, 40–41
  - performance comparison of frame materials, 136–38
  - spacer effects, 101, 102–3
  - tinted glass, 84*f*, 89–90
  - wood frame windows, 131
- ultraviolet radiation, 67–69, 73, 75
- U.S. Green Building Council, 22
- utility rebates, 28
- V
- vacuum glazing, 108–10
  - ventilation, 59
    - house design for, 156–59
    - sash operating types, 120
    - skylight and roof window features, 121
  - views through windows, 149–51
  - vinyl frames, 126, 131–33, 136–38
  - visible light, 73, 74–75
- W
- warm edge spacers, 16, 98, 102–3
  - water resistance, 71

- window installation, 138–42
  - weather conditions
    - air leakage and, 47, 125
    - see also* climate zones; wind conditions
  - weatherstripping, 16, 124–25
    - in sliding window sashes, 124
  - wind conditions
    - air leakage and, 47
    - heat loss control strategies, 168–69
    - structural capacity of windows, 71
    - ventilation design, 157–59
  - Window and Door Manufacturers Association, 221, 226
  - window selection. *see* selection, window
  - WINDOW 5 software, 65, 219
  - window technology, generally
    - future prospects, 16–17
    - historical evolution, 12–14
    - recent improvements, 15–16
  - wood frames, 126, 130–31, 134–35, 136–38
- Z
- Zero Energy Window, 17